

Cable ID	Summary	Test Limit	Length	Headroom	Date / Time
FPC-5004E-SOL	PASS	ISO11801 Channel Class D	183 ft	2.7 dB (NEXT)	10/24/2023 08:56 ☐
UPC-6004SE-L	PASS	ISO11801 Channel Class E	83 ft	8.0 dB (NEXT)	10/24/2023 08:58 ☐
FPC-5004E-L	PASS	ISO11801 Channel Class D	95 ft	13.2 dB (NEXT)	10/24/2023 08:59 ☐
FPC-5004E	PASS	ISO11801 Channel Class D	67 ft	3.2 dB (NEXT)	10/24/2023 09:04 ☐
UPC-5004E-SOL	PASS	ISO11801 Channel Class D	228 ft	10.4 dB (NEXT)	10/24/2023 09:09 ☐
UPC-6004SE-SO	PASS	ISO11801 Channel Class E	252 ft	3.7 dB (NEXT)	10/24/2023 09:11 ☐
UPC-6004SE-SOL	PASS	ISO11801 Channel Class E	252 ft	4.5 dB (NEXT)	10/24/2023 09:17 ☐

Total Length:	1160 ft
Number of Reports:	7
Number of Passing Reports:	7
Number of Failing Reports:	0
Number of Warning Reports:	0
Documentation Only:	0



Cable ID: FPC-5004E-SOL

Date / Time: 10/24/2023 08:56:27 □□

Headroom 2.7 dB (NEXT 36-45)

Test Limit: ISO11801 Channel Class D

Cable Type: Cat 5e FTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002


Length (ft)	[Pair 12]	182
Prop. Delay (ns), Limit 555	[Pair 36]	279
Delay Skew (ns), Limit 50	[Pair 36]	10
Resistance (ohms), Limit 25.0	[Pair 36]	12.8
Insertion Loss Margin (dB)	[Pair 78]	8.2
Frequency (MHz)	[Pair 78]	100.0
Limit (dB)	[Pair 78]	24.0



182 ft





Wire Map (T568B) PASS





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	36-45	36-45	36-45
NEXT (dB)	4.5	2.7	5.2	2.7
Freq. (MHz)	64.5	73.5	76.8	73.5
Limit (dB)	33.4	32.4	32.1	32.4
Worst Pair	45	36	45	36
PS NEXT (dB)	7.2	5.6	7.9	5.6
Freq. (MHz)	64.5	73.5	77.0	73.5
Limit (dB)	30.4	29.4	29.0	29.4





PASS	MAIN	SR	MAIN	SR
Worst Pair	36-78	45-78	36-78	45-78
ACR-F (dB)	24.5	24.9	24.5	24.9
Freq. (MHz)	92.8	90.0	93.0	90.0
Limit (dB)	18.1	18.3	18.0	18.3
Worst Pair	78	36	78	36
PS ACR-F (dB)	24.5	25.6	24.5	25.6
Freq. (MHz)	92.8	81.5	93.0	96.8
Limit (dB)	15.1	16.2	15.0	14.7



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	36-45	12-78	36-45
ACR-N (dB)	9.3	9.5	14.8	15.0
Freq. (MHz)	7.4	30.8	94.3	97.3
Limit (dB)	43.0	26.1	7.3	6.6
Worst Pair	78	45	78	45
PS ACR-N (dB)	11.5	12.4	17.5	17.7
Freq. (MHz)	7.5	12.9	94.3	97.3
Limit (dB)	39.9	34.0	4.3	3.6



PASS	MAIN	SR	MAIN	SR
Worst Pair	36	78	36	78
RL (dB)	4.8	4.6	10.0	4.6
Freq. (MHz)	15.1	6.1	99.3	6.1
Limit (dB)	17.0	17.0	10.0	17.0



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	



Cable ID: UPC-6004SE-L

Date / Time: 10/24/2023 08:58:05 □□

Headroom 8.0 dB (NEXT 12-78)

Test Limit: ISO11801 Channel Class E

Cable Type: Cat 6 UTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002



Length (ft)	[Pair 78]	83
Prop. Delay (ns), Limit 555	[Pair 36]	127
Delay Skew (ns), Limit 50	[Pair 36]	5
Resistance (ohms), Limit 25.0	[Pair 78]	12.5
Insertion Loss Margin (dB)	[Pair 36]	22.0
Frequency (MHz)	[Pair 36]	250.0
Limit (dB)	[Pair 36]	35.9



83 ft





Wire Map (T568B) PASS





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-45	12-78	12-78	12-78
NEXT (dB)	9.2	8.0	10.8	12.2
Freq. (MHz)	55.5	75.5	247.5	207.0
Limit (dB)	44.2	42.0	33.2	34.5
Worst Pair	12	78	12	36
PS NEXT (dB)	10.7	9.1	12.2	13.2
Freq. (MHz)	23.6	75.8	247.0	242.0
Limit (dB)	47.8	39.2	30.2	30.4





PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	78-12	45-36	12-78
ACR-F (dB)	12.1	12.1	14.0	13.4
Freq. (MHz)	70.0	70.0	249.0	232.0
Limit (dB)	26.4	26.4	15.3	15.9
Worst Pair	12	12	36	45
PS ACR-F (dB)	13.3	13.2	15.8	16.2
Freq. (MHz)	72.5	70.0	249.0	249.0
Limit (dB)	23.1	23.4	12.3	12.3



PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	36-45	12-78	12-36
ACR-N (dB)	12.2	13.3	33.0	35.0
Freq. (MHz)	4.1	3.3	247.5	243.0
Limit (dB)	58.6	60.5	-2.5	-2.0
Worst Pair	36	36	12	36
PS ACR-N (dB)	12.2	11.7	34.3	34.7
Freq. (MHz)	3.6	3.5	247.0	242.0
Limit (dB)	57.2	57.5	-5.4	-4.9



PASS	MAIN	SR	MAIN	SR
Worst Pair	78	12	36	12
RL (dB)	5.7	2.5	8.0	2.5
Freq. (MHz)	117.5	132.5	244.5	132.5
Limit (dB)	11.3	10.8	8.1	10.8



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	



Cable ID: FPC-5004E-L

Date / Time: 10/24/2023 08:59:50

Headroom 13.2 dB (NEXT 45-78)

Test Limit: ISO11801 Channel Class D

Cable Type: Cat 5e FTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002



Length (ft)	[Pair 12]	95
Prop. Delay (ns), Limit 555	[Pair 45]	149
Delay Skew (ns), Limit 50	[Pair 45]	9
Resistance (ohms), Limit 25.0	[Pair 78]	19.2
Insertion Loss Margin (dB)	[Pair 36]	12.8
Frequency (MHz)	[Pair 36]	100.0
Limit (dB)	[Pair 36]	24.0



95 ft



Wire Map (T568B)



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	45-78	36-78	36-78	36-78
NEXT (dB)	13.2	15.2	14.0	15.2
Freq. (MHz)	55.3	29.4	66.5	100.0
Limit (dB)	34.5	39.2	33.1	30.1
Worst Pair	78	78	36	78
PS NEXT (dB)	14.4	16.5	17.5	16.9
Freq. (MHz)	54.8	54.8	87.3	99.5
Limit (dB)	31.6	31.6	28.1	27.1









PASS	MAIN	SR	MAIN	SR
Worst Pair	36-78	78-36	36-78	78-36
ACR-F (dB)	28.3	27.5	28.3	27.5
Freq. (MHz)	99.8	99.8	99.8	99.8
Limit (dB)	17.4	17.4	17.4	17.4
Worst Pair	36	36	36	36
PS ACR-F (dB)	28.9	28.6	28.9	28.6
Freq. (MHz)	68.0	98.8	92.0	99.5
Limit (dB)	17.8	14.5	15.1	14.4

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-78	36-78	36-78	36-78
ACR-N (dB)	17.7	19.1	28.8	28.8
Freq. (MHz)	3.0	6.9	86.8	100.0
Limit (dB)	51.6	43.8	8.9	6.1
Worst Pair	78	36	36	36
PS ACR-N (dB)	19.1	20.7	29.7	30.1
Freq. (MHz)	3.0	6.9	87.3	100.0
Limit (dB)	48.6	40.8	5.8	3.1

PASS	MAIN	SR	MAIN	SR
Worst Pair	36	78	36	36
RL (dB)	5.0	6.2	5.0	11.3
Freq. (MHz)	97.8	5.3	97.8	100.0
Limit (dB)	10.1	17.0	10.1	10.0

Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	





Cable ID: FPC-5004E

Date / Time: 10/24/2023 09:04:03

Headroom 3.2 dB (NEXT 12-78)

Test Limit: ISO11801 Channel Class D

Cable Type: Cat 5e FTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002



Length (ft)	[Pair 78]	67
Prop. Delay (ns), Limit 555	[Pair 36]	103
Delay Skew (ns), Limit 50	[Pair 36]	5
Resistance (ohms), Limit 25.0	[Pair 78]	16.5
Insertion Loss Margin (dB)	[Pair 36]	15.5
Frequency (MHz)	[Pair 36]	100.0
Limit (dB)	[Pair 36]	24.0



67 ft





Wire Map (T568B) PASS





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	12-78	12-78	12-78
NEXT (dB)	5.7	3.2	6.4	3.2
Freq. (MHz)	31.0	75.3	75.8	75.3
Limit (dB)	38.8	32.2	32.2	32.2
Worst Pair	45	12	12	12
PS NEXT (dB)	7.9	5.8	9.1	5.8
Freq. (MHz)	31.8	74.8	75.8	75.3
Limit (dB)	35.6	29.3	29.2	29.2





PASS	MAIN	SR	MAIN	SR
Worst Pair	36-12	12-36	12-36	36-12
ACR-F (dB)	19.3	19.3	21.6	21.7
Freq. (MHz)	2.6	2.6	97.0	98.3
Limit (dB)	49.0	49.0	17.7	17.6
Worst Pair	36	36	36	36
PS ACR-F (dB)	20.3	20.1	22.0	22.7
Freq. (MHz)	3.0	2.9	99.8	100.0
Limit (dB)	44.9	45.2	14.4	14.4



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	12-78	12-78	12-78
ACR-N (dB)	12.4	11.5	20.0	16.7
Freq. (MHz)	9.6	8.5	75.8	75.3
Limit (dB)	40.3	41.6	11.5	11.6
Worst Pair	78	12	12	12
PS ACR-N (dB)	13.2	12.3	22.5	19.2
Freq. (MHz)	10.3	6.9	75.8	75.3
Limit (dB)	36.6	40.8	8.5	8.6



PASS	MAIN	SR	MAIN	SR
Worst Pair	36	12	12	78
RL (dB)	7.6	7.3	12.7	10.0
Freq. (MHz)	11.0	11.9	98.3	79.5
Limit (dB)	17.0	17.0	10.1	11.0



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	



Cable ID: UPC-5004E-SOL

Date / Time: 10/24/2023 09:09:56 □□

Headroom 10.4 dB (NEXT 12-45)

Test Limit: ISO11801 Channel Class D

Cable Type: Cat 5e UTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002



Length (ft)	[Pair 78]	228
Prop. Delay (ns), Limit 555	[Pair 36]	347
Delay Skew (ns), Limit 50	[Pair 36]	11
Resistance (ohms), Limit 25.0	[Pair 36]	21.7
Insertion Loss Margin (dB)	[Pair 36]	5.8
Frequency (MHz)	[Pair 36]	100.0
Limit (dB)	[Pair 36]	24.0



228 ft





Wire Map (T568B) PASS





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-45	12-78	45-78	12-78
NEXT (dB)	10.4	10.7	11.1	14.8
Freq. (MHz)	41.3	19.5	67.0	88.0
Limit (dB)	36.7	42.2	33.1	31.0
Worst Pair	45	78	78	12
PS NEXT (dB)	12.2	11.6	15.4	16.0
Freq. (MHz)	41.3	19.1	96.8	86.8
Limit (dB)	33.7	39.3	27.3	28.1





PASS	MAIN	SR	MAIN	SR
Worst Pair	78-12	12-78	78-12	12-78
ACR-F (dB)	6.0	5.7	6.2	5.7
Freq. (MHz)	62.0	61.8	100.0	100.0
Limit (dB)	21.6	21.6	17.4	17.4
Worst Pair	12	78	12	78
PS ACR-F (dB)	8.7	8.8	8.9	9.1
Freq. (MHz)	62.0	62.0	100.0	100.0
Limit (dB)	18.6	18.6	14.4	14.4



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	12-78	12-78	12-78
ACR-N (dB)	11.2	12.2	20.0	20.2
Freq. (MHz)	2.1	6.4	96.8	88.0
Limit (dB)	54.0	44.5	6.7	8.6
Worst Pair	12	78	78	78
PS ACR-N (dB)	13.0	13.8	21.1	21.7
Freq. (MHz)	2.1	6.4	96.8	88.0
Limit (dB)	51.0	41.5	3.7	5.6



PASS	MAIN	SR	MAIN	SR
Worst Pair	78	78	78	78
RL (dB)	5.1	6.0	5.1	6.0
Freq. (MHz)	88.5	76.8	88.5	76.8
Limit (dB)	10.5	11.1	10.5	11.1



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	



Cable ID: UPC-6004SE-SO

Date / Time: 10/24/2023 09:11:54 □□

Headroom 3.7 dB (NEXT 12-78)

Test Limit: ISO11801 Channel Class E

Cable Type: Cat 6 UTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002



Length (ft)	[Pair 78]	252
Prop. Delay (ns), Limit 555	[Pair 36]	386
Delay Skew (ns), Limit 50	[Pair 36]	15
Resistance (ohms), Limit 25.0	[Pair 45]	20.3
Insertion Loss Margin (dB)	[Pair 45]	11.3
Frequency (MHz)	[Pair 45]	250.0
Limit (dB)	[Pair 45]	35.9



252 ft



Wire Map (T568B) PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	45-78	12-78	12-45	12-78
NEXT (dB)	4.6	3.7	7.7	3.7
Freq. (MHz)	27.8	234.5	204.5	234.5
Limit (dB)	49.3	33.6	34.6	33.6
Worst Pair	78	12	12	12
PS NEXT (dB)	6.3	5.8	9.2	5.8
Freq. (MHz)	27.5	235.0	204.5	235.0
Limit (dB)	46.6	30.6	31.7	30.6









PASS	MAIN	SR	MAIN	SR
Worst Pair	78-12	12-78	36-45	12-78
ACR-F (dB)	3.4	3.5	5.9	4.5
Freq. (MHz)	171.0	171.0	235.5	199.0
Limit (dB)	18.6	18.6	15.8	17.3
Worst Pair	12	78	45	78
PS ACR-F (dB)	6.4	5.8	8.0	6.7
Freq. (MHz)	171.0	171.0	235.5	199.0
Limit (dB)	15.6	15.6	12.8	14.3

PASS	MAIN	SR	MAIN	SR
Worst Pair	45-78	12-45	12-45	12-78
ACR-N (dB)	7.4	9.6	17.7	15.8
Freq. (MHz)	3.1	5.9	204.5	234.5
Limit (dB)	60.8	55.3	2.5	-1.1
Worst Pair	45	12	45	12
PS ACR-N (dB)	8.1	9.3	19.3	17.7
Freq. (MHz)	3.3	6.0	203.0	235.0
Limit (dB)	58.0	52.6	-0.3	-4.1

PASS	MAIN	SR	MAIN	SR
Worst Pair	45	45	12	36
RL (dB)	5.4	7.4	10.1	9.9
Freq. (MHz)	4.0	4.1	233.0	250.0
Limit (dB)	19.0	19.0	8.3	8.0

Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	





Cable ID: UPC-6004SE-SOL

Date / Time: 10/24/2023 09:17:43 □□

Headroom 4.5 dB (NEXT 12-78)

Test Limit: ISO11801 Channel Class E

Cable Type: Cat 6 UTP

Operator: JACK

Software Version: 2.7400

Limits Version: 1.9300

NVP: 69.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 2433075

Remote S/N: 2433076

Main Adapter: DTX-CHA002

Remote Adapter: DTX-CHA002



Length (ft)	[Pair 78]	252
Prop. Delay (ns), Limit 555	[Pair 36]	386
Delay Skew (ns), Limit 50	[Pair 36]	15
Resistance (ohms), Limit 25.0	[Pair 36]	11.3
Insertion Loss Margin (dB)	[Pair 36]	11.5
Frequency (MHz)	[Pair 36]	250.0
Limit (dB)	[Pair 36]	35.9



252 ft





Wire Map (T568B)
PASS





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	45-78	12-78	12-45
NEXT (dB)	4.5	5.5	4.5	7.6
Freq. (MHz)	235.0	27.5	235.0	203.0
Limit (dB)	33.6	49.3	33.6	34.7
Worst Pair	12	45	12	45
PS NEXT (dB)	6.6	6.5	6.6	8.7
Freq. (MHz)	235.0	27.4	235.0	203.5
Limit (dB)	30.6	46.7	30.6	31.7





PASS	MAIN	SR	MAIN	SR
Worst Pair	12-78	78-12	12-78	78-12
ACR-F (dB)	2.7	2.6	2.9	2.8
Freq. (MHz)	146.5	146.5	200.0	200.0
Limit (dB)	19.9	19.9	17.2	17.2
Worst Pair	78	12	78	12
PS ACR-F (dB)	5.3	5.4	5.3	5.4
Freq. (MHz)	200.0	200.0	200.0	200.0
Limit (dB)	14.2	14.2	14.2	14.2



PASS	MAIN	SR	MAIN	SR
Worst Pair	12-45	36-45	12-78	12-45
ACR-N (dB)	9.6	7.6	16.5	18.0
Freq. (MHz)	5.8	9.0	235.0	204.5
Limit (dB)	55.5	51.1	-1.1	2.5
Worst Pair	12	36	12	45
PS ACR-N (dB)	10.4	8.6	18.6	19.0
Freq. (MHz)	5.9	8.6	235.0	203.5
Limit (dB)	52.8	49.0	-4.1	-0.3



PASS	MAIN	SR	MAIN	SR
Worst Pair	36	78	36	78
RL (dB)	10.2	9.2	10.2	9.2
Freq. (MHz)	249.5	241.0	249.5	241.0
Limit (dB)	8.0	8.2	8.0	8.2



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	